Technical Section

All Heritage Clay Tiles are independently tested and approved by Lucideon Building Technology who has fifty years experience in conducting material tests. The tests involve subjecting the tiles to frequent cycles of soaking, freezing and thawing. The criteria for achieving a pass is stringent as the rigorous tests really push the tiles to the limit.

Our current test results can be viewed on our website at **www.heritagetiles.co.uk**. We are proud of the high pass rates our tiles achieve and encourage our customers to compare these results with other companies when making a choice.

Description	Roof	Vertical
Minimum Roof Pitch	35 o	75 °
Headlap (Minimum)	65mm	38mm
Batten spacing at maximum gauge	100mm	114mm
Size of tile	265 x 165mm	265 x 165mm
Covering Capacity	60 per m2	53 per m2
Cover width	165mm	165mm
Weight as laid	75kg per m2	66.25kg per m2
Battens per M2	10m	8.7m
Batten Size	38 x 25mm	38 x 25mm
Recomended nail type	40 x 2.65mm Alloy clout	40 x 2.65mm Alloy clout

Recommendations

Tiles to be laid in accordance with BS 5534. Tiles to be drawn from a minimum of 3 separate pallets to ensure best effect, tiles are delivered on non returnable shroud wrapped pallets. Pallets on site should be on firm, dry and level ground, no more that 2 pallets high due to limitations of the print process, colours should be selected from actual samples.

Quality Assurance

Heritage tiles conform to BS EN 1304:2005 and BS EN 539-2:2013 and are manufactured under a Quality Management System, which meets the requirements of ISO:9001 2008. Our materials and finished products are tested by our quality control staff at every stage of the production process.

Heritage Clay Tiles Ltd
Temple Park, Priory Road, Strood, Kent ME2 2EG
tel: 01634 471322

email: sales@heritagetiles.co.uk web: www.heritagetiles.co.uk

Fittings





External Angle















Hogs Back Ridge

Many More Available

Available in

Red

Medium

Dark