

# Kent Clay Peg Tiles



**50**  
Year  
Guarantee

## Kent Clay Peg Tiles

Peg tiles are normally provided with two holes at the head of the tile, one on either side of the vertical centre-line of the tile where the joint of the upper two tiles occurs when laid. These holes are formed by simply poking through the tile with a suitable slightly tapered device in such a way as to avoid splitting the unburnt clay.

Description	Roof	Vertical
Minimum Roof Pitch	35°	75°
Headlap (Minimum)	65mm	38mm
Batten Spacing at Maximum Gauge	100mm	114mm
Size of Tile	250 x 150mm	250 x 150mm
Covering Capacity	72 per m <sup>2</sup>	64 per m <sup>2</sup>
Cover Width	250 x 150mm	250 x 150mm
Weight as Laid	72 kg per m <sup>2</sup>	64 kg per m <sup>2</sup>
Battens per M <sup>2</sup>	10m	8.7m
Batten Size	38 x 25mm	38 x 25mm
Recommended Nail Type	40 x 2.65mm Alloy Clout or Wooden Pegs	40 x 2.65mm Alloy Clout or Wooden Pegs

### Heritage Clay Tiles Ltd

Hangman's Wood Ind Park  
Stifford Road, South Ockendon  
Essex RM15 6RL  
tel: 01708 853 953  
fax: 01708 851 852  
email: [sales@heritagetiles.co.uk](mailto:sales@heritagetiles.co.uk)  
website: [www.heritagetiles.co.uk](http://www.heritagetiles.co.uk)